

SAIC, TEZPUR UNIVERSITY
Glass Blowing Workshop Charge rate

| Sl no | Item/Job description | Per Job/Item | External users charge rate | | Internal users Charge Rates (RS) |
|-------|--|--------------|----------------------------|-------------------------------|-------------------------------------|
| | | | Industry (RS) | Educational institute (RS) | |
| 1 | POLENSKES apparatus (R M value apparatus) for determination of butter fat and analysis of oil , fats ,waxes | 1 | 4055 | 2433 | 811 |
| 2 | Adapter CLAISEN head, sloping cone | | | | |
| | A) Flask B-14/23 cone condenser B-14/23 | 1 | 1275 | 765 | 255 |
| | B) Flask B-19/26 cone condenser B-19/26 | 1 | 1435 | 861 | 287 |
| | C) Flask B-24/29 cone condenser B-19/26 | 1 | 1465 | 879 | 293 |
| | D) Flask B-34/35 cone condenser B-19/26 | 1 | 1735 | 1041 | 347 |
| 3 | Adapter expansion | | | | |
| | A) Socket 19/26 cone 14/23 | 1 | 435 | 261 | 87 |
| | B) Socket 24/29 cone 14/23 | 1 | 460 | 276 | 92 |
| | C) Socket 29/32 cone 19/26 | 1 | 570 | 342 | 114 |
| | D) Socket 24/29 cone 19/26 | 1 | 460 | 276 | 92 |
| | E) Socket 34/35 cone 24/29 | 1 | 710 | 426 | 142 |
| 4 | Adapter, multiple with two neck (Parallel) | | | | |
| | A) Socket 14/23 cone 14/23 | 1 | 815 | 489 | 163 |
| | B) Socket 19/26 cone 19/26 | 1 | 950 | 570 | 190 |
| | C) Socket 19/26 cone 24/29 | 1 | 950 | 570 | 190 |
| | D) Socket 24/29 cone 24/29 | 1 | 1140 | 684 | 228 |
| | E) Socket 19/26 cone 34/35 | 1 | 1220 | 732 | 244 |
| 5 | Adapter, multiple with two necks (45° angle) | | | | |
| | A) Socket 19/26 cone 19/26 | 1 | 950 | 570 | 190 |
| | B) Socket 19/26 cone 24/29 | 1 | 950 | 570 | 190 |
| | C) Socket 19/26 cone 34/35 | 1 | 1220 | 732 | 244 |
| 6 | Adapter, multiple with three necks (angle, parallel & Cone) | | | | |
| | A) Socket 19/26 cone 24/29 | 1 | 1385 | 831 | 277 |
| | B) Socket 19/26 cone 29/32 | 1 | 1600 | 960 | 320 |
| | C) Socket 19/26 cone 34/35 | 1 | 1630 | 978 | 326 |
| 7 | Adapter receiving plain bend short | | | | |
| | A) Socket 14/23 | 1 | 410 | 246 | 82 |
| | B) Socket 24/29 | 1 | 460 | 276 | 92 |
| | C) Socket 29/32 | 1 | 545 | 327 | 109 |
| | D) Socket 34/35 | 1 | 710 | 426 | 142 |
| | E) Socket 40/38 | 1 | 1060 | 636 | 212 |

| SI no | Item/Job description | External users charge rate | | | Internal users Charge Rates (RS) |
|-------|--|----------------------------|------------------|-------------------------------|---|
| | | Per Job/Item | Industry (RS) | Educational institute (RS) | |
| 8 | Adapter receiving plain bend long | | | | |
| | A) Socket 14/23 | 1 | 410 | 246 | 82 |
| | B) Socket 19/26 | 1 | 435 | 261 | 87 |
| | C) Socket 24/29 | 1 | 460 | 276 | 92 |
| | D) Socket 34/35 | 1 | 710 | 426 | 142 |
| | E) Socket 40/38 | 1 | 1060 | 636 | 212 |
| | F) Socket 45/40 | 1 | 1360 | 816 | 272 |
| 9 | Adapter receiving straight deli verily | | | | |
| | A) Socket 14/23 | 1 | 410 | 246 | 82 |
| | B) Socket 19/26 | 1 | 435 | 261 | 87 |
| | C) Socket 24/29 | 1 | 460 | 276 | 92 |
| | D) Socket 29/32 | 1 | 545 | 327 | 109 |
| | E) Socket 34/35 | 1 | 710 | 426 | 142 |
| 10 | Adapter receiving plain bend | | | | |
| | A) Socket 19/26 cone 19/26 | 1 | 675 | 405 | 135 |
| | B) Socket 19/26 cone 24/29 | 1 | 710 | 426 | 142 |
| | C) Socket 24/29 cone 24/29 | 1 | 785 | 471 | 157 |
| | D) Socket 34/35 cone 34/35 | 1 | 1085 | 651 | 217 |
| 11 | Adapter receiving bend with vent | | | | |
| | A) Socket 14/23 cone 14/23 | 1 | 625 | 375 | 125 |
| | B) Socket 19/26 cone 19/26 | 1 | 735 | 441 | 147 |
| | C) Socket 19/26 cone 24/29 | 1 | 735 | 441 | 147 |
| | D) Socket 24/29 cone 24/29 | 1 | 840 | 504 | 168 |
| | E) Socket 34/35 cone 34/35 | 1 | 1140 | 684 | 228 |
| 12 | Adapter receiving (bend with vacuum connection) | | | | |
| | A) Socket 14/23 cone 14/23 | 1 | 840 | 504 | 168 |
| | B) Socket 19/26 cone 19/26 | 1 | 895 | 537 | 179 |
| | C) Socket 19/26 cone 24/29 | 1 | 950 | 570 | 190 |
| | D) Socket 24/29 cone 24/29 | 1 | 1060 | 636 | 212 |
| | E) Socket 34/35 cone 34/35 | 1 | 1385 | 554 | 277 |
| 13 | Adapter receiving(straight with vacuum connection) | | | | |
| | A) Socket 19/26 cone 19/26 | 1 | 1085 | 651 | 217 |
| | B) Socket 19/26 cone 24/29 | 1 | 950 | 570 | 190 |
| | C) Socket 24/29 cone 24/29 | 1 | 1060 | 636 | 212 |
| | D) Socket 34/35 cone 34/35 | 1 | 1140 | 684 | 228 |
| 14 | Adapter receiving bent with connection | | | | |
| | A) Socket 14/23 cone 14/23 | 1 | 870 | 522 | 174 |
| | B) Socket 19/26 cone 19/26 | 1 | 950 | 570 | 190 |
| | C) Socket 19/26 cone 24/29 | 1 | 975 | 585 | 195 |
| 15 | Adapter receiver multi limp vacuum socket B-19 , cone B-14 | 1 | 3500 | 2100 | 700 |
| 16 | Adapter receiver vertical delivery | 1 | 850 | 510 | 170 |
| 17 | Adapter receiver sloping delivery | 1 | 850 | 510 | 170 |

| SI no | Item/Job description | External users charge rate | | | Internal users Charge Rates (RS) |
|-------|---|----------------------------|------------------|-------------------------------|---|
| | | Per Job/Item | Industry (RS) | Educational institute (RS) | |
| 18 | Adapter reduction | | | | |
| | A) Socket 14/23 cone 19/26 | 1 | 350 | 210 | 70 |
| | B) Socket 14/23 cone 29/32 | 1 | 460 | 276 | 92 |
| | C) Socket 19/26 cone 29/32 | 1 | 460 | 276 | 92 |
| | D) Socket 19/26 cone 34/35 | 1 | 515 | 309 | 103 |
| | E) Socket 19/26 cone 40/38 | 1 | 710 | 426 | 142 |
| | F) Socket 19/26 cone 45/40 | 1 | 840 | 504 | 168 |
| | G) Socket 24/29 cone 34/35 | 1 | 570 | 342 | 114 |
| | H) Socket 24/29 cone 45/40 | 1 | 870 | 522 | 174 |
| | I) Socket 29/32 cone 34/35 | 1 | 650 | 390 | 130 |
| | J) Socket 29/32 cone 40/38 | 1 | 815 | 489 | 163 |
| | K) Socket 34/35 cone 40/38 | 1 | 895 | 537 | 179 |
| 19 | Adapter (socket to cone with T connection) | | | | |
| | A) Socket 14/23 cone 14/23 | 1 | 460 | 276 | 92 |
| | B) Socket 14/23 cone 19/26 | 1 | 510 | 306 | 102 |
| | C) Socket 19/26 cone 24/29 | 1 | 570 | 342 | 114 |
| | D) Socket 19/26 cone 34/35 | 1 | 740 | 444 | 148 |
| | E) Socket 24/29 cone 34/35 | 1 | 820 | 492 | 164 |
| | F) Socket 34/35 cone 34/35 | 1 | 950 | 570 | 190 |
| 20 | Adapter still head recovery bend cone flask to cone condenser(sloping) | | | | |
| | A) F cone 14/23 cone 14/23 | 1 | 570 | 342 | 114 |
| | B) F cone 24/29 cone 14/23 | 1 | 735 | 441 | 147 |
| | C) F cone 19/26 cone 19/26 | 1 | 650 | 390 | 130 |
| | D) F cone 24/29 cone 19/26 | 1 | 815 | 489 | 163 |
| | E) F cone 29/32 cone 19/26 | 1 | 870 | 522 | 174 |
| | F) F cone 34/35 cone 24/29 | 1 | 1035 | 621 | 207 |
| | G) F cone 34/35 cone 34/35 | 1 | 1110 | 666 | 222 |
| | H) F cone 29/32 cone 29/32 | 1 | 895 | 537 | 179 |
| 21 | Still head recovery bend vertical (flask cone to condenser cone) | | | | |
| | A) F cone 14/23 cone 14/23 | 1 | 710 | 426 | 142 |
| | B) F cone 19/26 cone 19/26 | 1 | 870 | 522 | 174 |
| | C) F cone 24/29 cone 14/23 | 1 | 1000 | 600 | 200 |
| | D) F cone 24/29 cone 24/29 | 1 | 1140 | 684 | 228 |
| | E) F cone 34/35 cone 34/35 | 1 | 1735 | 1041 | 347 |
| 22 | Still head plain(sloping with B-14/23) socket cone fitting | | | | |
| | A) F cone 14/23 cone 14/23 | 1 | 870 | 522 | 174 |
| | B) F cone 19/26 cone 19/26 | 1 | 1000 | 600 | 200 |
| | C) F cone 24/29 cone 19/26 | 1 | 1035 | 621 | 207 |
| | D) F cone 29/32 cone 19/26 | 1 | 1195 | 717 | 239 |
| | E) F cone 34/35 cone 19/26 | 1 | 1300 | 780 | 260 |
| | F) F cone 24/29 cone 24/29 | 1 | 1170 | 702 | 234 |

| SI no | Item/Job description | External users charge rate | | | Internal users Charge Rates (RS) |
|-------|--|----------------------------|------------------|-------------------------------|-------------------------------------|
| | | Per Job/Item | Industry (RS) | Educational institute (RS) | |
| 23 | Splash head adapter cone fitting flask 24/29 cone fitting condenser 19/26 | 1 | 1220 | 732 | 244 |
| 24 | Adapter splash head sloping cone fitting | | | | |
| | A) F cone 19/26 C cone 19/26 | 1 | 1170 | 702 | 234 |
| | B) F cone 24/29 C cone 19/26 | 1 | 1220 | 732 | 244 |
| | C) F cone 34/35 C cone 24/29 | 1 | 1385 | 831 | 277 |
| | D) F cone 34/35 C cone 34/35 | 1 | 1435 | 861 | 287 |
| | E) F cone 24/29 C cone 24/29 | 1 | 1250 | 750 | 250 |
| 25 | Adapter splash head vertical cone fitting | | | | |
| | A) F cone 19/26 C cone 19/26 | 1 | 1545 | 927 | 309 |
| | B) F cone 24/29 C cone 19/26 | 1 | 1575 | 945 | 315 |
| | C) F cone 24/29 C cone 24/29 | 1 | 1655 | 993 | 331 |
| 26 | Adapter with cone Straight /Right connection | | | | |
| | A) Socket 14/23 | 1 | 340 | 204 | 68 |
| | B) Socket 19/26 | 1 | 390 | 234 | 78 |
| | C) Socket 24/29 | 1 | 425 | 255 | 85 |
| | D) Socket 34/35 | 1 | 645 | 387 | 129 |
| 27 | Inter changeable head | | | | |
| | A) cone 34/35 | 1 | 1750 | 1050 | 350 |
| | B) cone 24/29 | 1 | 1400 | 840 | 280 |
| | C) cone 40/38 | 1 | 2000 | 1200 | 400 |
| 28 | Bottle wash | | | | |
| | A) IC joint 500 ml | 1 | 2170 | 1302 | 434 |
| | B) IC joint 250 ml | 1 | 1885 | 1131 | 377 |
| 29 | Bottle wash sloping type (1000ml) | 1 | 3255 | 1953 | 651 |
| 30 | Calcium chloride U tube | | | | |
| | A) 100 mm height OD 12mm | 1 | 330 | 198 | 66 |
| | B) 125 mm height OD 15mm | 1 | 475 | 285 | 95 |
| 31 | Column chromatography plain | | | | |
| | A) 10 mm bore 20 cm length | 1 | 235 | 141 | 47 |
| | B) 15 mm bore 30 cm length | 1 | 415 | 249 | 83 |
| | C) 20 mm bore 50 cm length | 1 | 775 | 465 | 155 |
| | D) 25 mm bore 60 cm length | 1 | 955 | 573 | 191 |
| | E) 40 mm bore 60 cm length | 1 | 2250 | 1350 | 450 |
| | F) 48 mm bore 100 cm length | 1 | 5115 | 3069 | 1023 |
| 32 | Pipettes | | | | |
| | A) Capacity 10 ml | 1 | 1085 | 651 | 217 |
| | B) Capacity 20 ml | 1 | 1240 | 744 | 248 |
| | C) Capacity 25 ml | 1 | 1135 | 681 | 227 |
| 33 | Flask pear shaped VIGREUX | | | | |
| | A) neck 25 ml socket 14/23 cone 14/23 | 1 | 1495 | 897 | 299 |
| | B) neck 50 ml socket 14/23 cone 14/23 | 1 | 1600 | 960 | 320 |

| SI no | Item/Job description | External users charge rate | | | Internal users Charge Rates (RS) |
|-------|--|----------------------------|------------------|-------------------------------|---|
| | | Per Job/Item | Industry (RS) | Educational Institute (RS) | |
| | C) neck 100 ml socket 14/23 cone 14/23 | 1 | 1955 | 1173 | 391 |
| 34 | Pipette alcohol (middle bulb type) | 1 | 180 | 108 | 36 |
| 35 | Air condensers | | | | |
| | A) Socket 14/23 cone 14/23 length 200 mm | 1 | 680 | 408 | 136 |
| | B) Socket 19/26 cone 19/26 length 200 mm | 1 | 815 | 489 | 163 |
| | C) Socket 24/29 cone 24/29 length 250 mm | 1 | 1110 | 666 | 222 |
| | D) Socket 19/26 cone 19/26 length 400 mm | 1 | 1250 | 750 | 250 |
| | E) Socket 35/34 cone 35/34 length 500 mm | 1 | 3095 | 1857 | 619 |
| 36 | Lie big condensers | | | | |
| | A) Socket 24/29 to 24/29 cone length 200 mm | 1 | 1290 | 774 | 258 |
| | B) Socket 19/26 to 19/26 cone length 300 mm | 1 | 1395 | 837 | 279 |
| | C) Socket 24/29 to 24/29 cone length 350 mm | 1 | 1655 | 993 | 331 |
| | D) Socket 24/29 to 24 /29 cone length 400 mm | 1 | 1735 | 1041 | 347 |
| | E) Socket 24/29 to 24/29 cone length 750 mm | 1 | 3420 | 2052 | 684 |
| 37 | ALLIHN condensers | | | | |
| | A) 5 number bulb 200 mm long 34/35 cone | 1 | 1755 | 1053 | 351 |
| | B) 5 number bulb 400 mm long 24/29 cone | 1 | 2610 | 1566 | 522 |
| 38 | Coil condensers dubble | 1 | 6200 | 3720 | 1240 |
| 39 | Flasks pear,VIGREUX 50 ml socket 14/23 cone 14/23,two neck | 1 | 1140 | 684 | 228 |
| 40 | Flasks CLAISEN | | | | |
| | A) pear shaped 25 ml 14/23 socket cone 14/23 | 1 | 1385 | 831 | 277 |
| | B) pear shaped 50 ml 14/23 socket cone 14/23 | 1 | 1465 | 879 | 293 |
| | C) pear shaped 100 ml 14/23 socket cone 14/23 | 1 | 1795 | 1077 | 359 |
| 41 | Flask distillation | | | | |
| | A) side tube 50 ml | 1 | 650 | 390 | 130 |
| | B) side tube 100 ml | 1 | 785 | 471 | 157 |
| 42 | Flasks filtering | | | | |
| | A) 100 ml | 1 | 905 | 543 | 181 |
| | B) 250 ml | 1 | 1475 | 885 | 295 |

| SI no | Item/Job description | External users charge rate | | | Internal users Charge Rates (RS) |
|-------|--|----------------------------|------------------|-------------------------------|---|
| | | Per Job/Item | Industry (RS) | Educational Institute (RS) | |
| 43 | Perkins inter mediate receiver | | | | |
| | A) socket 14/23 cone 14/23 | 1 | 4450 | 2670 | 890 |
| | B) socket 19/26 cone 19/26 | 1 | 4585 | 2751 | 917 |
| | C) socket 19/26 cone 24/29 | 1 | 4615 | 2769 | 923 |
| 44 | Drying tube | | | | |
| | A) cone 14/23 | 1 | 440 | 264 | 88 |
| | B) cone 19/26 | 1 | 490 | 294 | 98 |
| | C) cone 24/29 | 1 | 515 | 309 | 103 |
| 45 | U Tube | | | | |
| | A) with two socket 14/23 | 1 | 925 | 555 | 185 |
| | B) with two socket 19/26 | 1 | 1035 | 621 | 207 |
| 46 | Pressure equalizing pars hap funnels, Stop cock and steam | | | | |
| | A) with cone 19/26, socket 19/26—(100 ml) | 1 | 2790 | 1674 | 558 |
| | B) with cone 24/29, socket 24/29—(100 ml) | 1 | 2970 | 1782 | 594 |
| | C) with cone 19/26, socket 19/26—(250 ml) | 1 | 3100 | 1860 | 620 |
| 47 | Pressure equalizing pars hap funnels | | | | |
| | A) (250ml) cylindrical socket 19/26 cone 19/26 | 1 | 3360 | 2016 | 672 |
| | B) (500ml) cylindrical socket 19/26 cone 19/26 | 1 | 4650 | 2790 | 930 |
| | C) (250ml) cylindrical socket 24/29 cone 24/29 | 1 | 3435 | 2061 | 687 |
| | D) (500ml) cylindrical socket 24/29 cone 24/29 | 1 | 5530 | 3318 | 1106 |
| 48 | Dropping funnels (Cylindrical) | | | | |
| | A) with stop cock, socket 19/26 cone 19/26 (250 ml) | 1 | 2455 | 1473 | 491 |
| | B) with stop cock, socket 19/26 cone 19/26 (100 ml) | 1 | 1785 | 1071 | 357 |
| 49 | Dropping funnels -24/29 cone and stop cock cylindrical 100 ml | 1 | 2015 | 1209 | 403 |
| 50 | Filter apparatus | | | | |
| | A) 250 ml Sintered disk 80 ml joined 24/29 | 1 | 3745 | 2247 | 749 |
| 51 | Reflux assembly consist 500ml multiple adapter two neck ,stirrer guide | 1 | 6925 | 4155 | 1385 |
| 52 | Reaction assembly R B500ml lie big condensers 400mm adapter Tconnection ,separating funnels 100ml and stopper | 1 | 5815 | 3489 | 1163 |
| 53 | KJELDAHL distillation assembly R . B 1000 ml multiple adapter two neck , splash head , vertical lie big condenser receiver adapter and dropping funnel 100ml | 1 | 8630 | 5178 | 1726 |

| SI no | Item/Job description | External users charge rate | | | Internal users Charge Rates (RS) |
|-------|--|----------------------------|------------------|-------------------------------|---|
| | | Per Job/Item | Industry (RS) | Educational Institute (RS) | |
| 54 | Solvent recovery assembly R .B 250 ml lie big condenser 400mm R .B 250 ml | 1 | 5450 | 3270 | 1090 |
| 55 | Chromatography assembly | 1 | 10075 | 6045 | 2015 |
| 56 | Chromatography columns integral sintered disc without stop cock | | | | |
| | A) Extractor length 15 cm disc 10 mm | 1 | 775 | 465 | 155 |
| | B) Extractor length 20 cm disc 15 mm | 1 | 930 | 558 | 186 |
| | C) Extractor length 30 cm disc 15 mm | 1 | 1085 | 651 | 217 |
| | D) Extractor length 40 cm disc 30 mm | 1 | 2120 | 1272 | 424 |
| | E) Extractor length 40cm disc 20mm | 1 | 1445 | 867 | 289 |
| | F) Extractor length 50 cm disc 30 mm | 1 | 2275 | 1365 | 455 |
| | G) Extractor length 50 cm disc 40 mm | 1 | 3515 | 2109 | 703 |
| | H) Extractor length 60 cm disc 40 mm | 1 | 3875 | 2325 | 775 |
| | I) Extractor length 100 cm disc 40 mm | 1 | 5165 | 3099 | 1033 |
| 57 | Chromatography columns without integral sintered disc and glass stop cock | | | | |
| | A) Extractor length 15 cm disc 10mm | 1 | 1550 | 930 | 310 |
| | B) Extractor length 20cm disc 15 mm | 1 | 1550 | 930 | 310 |
| | C) Extractor length 30cm disc 15 mm | 1 | 1680 | 1008 | 336 |
| | D) Extractor length 40 cm disc 20 mm | 1 | 1860 | 1116 | 372 |
| | E) Extractor length 50 cm disc 30 mm | 1 | 2740 | 1644 | 548 |
| | F) Extractor length 50 cm disc 40 mm | 1 | 4340 | 2604 | 868 |
| | G) Extractor length 60 cm disc 40mm | 1 | 4495 | 2697 | 899 |
| | H) Extractor length 100 cm disc 40 mm | 1 | 5815 | 3489 | 1163 |
| 58 | Gas trap | | | | |
| | A) size 40 mm length 30 cm | 1 | 2250 | 1350 | 450 |
| | B) size 30 mm length 20 cm | 1 | 1250 | 750 | 250 |
| | C) size 25 mm length 15 cm | 1 | 750 | 450 | 150 |
| 59 | Bubbler | | | | |
| | A) size 40mm length 30 cm | 1 | 2250 | 1350 | 450 |
| | B) size 30mm length 20 cm | 1 | 1500 | 900 | 300 |
| | C) size 25mm length 15 cm | 1 | 750 | 450 | 150 |
| 60 | Reactor 30 cm long and reactor head with joined size 30mm | 1 | 7000 | 4200 | 1400 |
| 61 | Volatile reactor 90cm long both side with B34 joint pair | 1 | 7500 | 4500 | 1500 |
| 62 | Y- tube connector 8mm | 1 | 215 | 129 | 43 |
| 63 | T- connector with corrugation 8mm | 1 | 215 | 129 | 43 |
| 64 | U- tube 8mm | 1 | 205 | 123 | 41 |
| 65 | Chromatography columns plain with stop cock | | | | |
| | A) Extractor length 20 cm, diameter 10 mm | 1 | 775 | 465 | 155 |
| | B) Extractor length 30 cm, diameter 15 mm | 1 | 980 | 588 | 196 |
| | C) Extractor length 50 cm, diameter 20 mm | 1 | 1110 | 666 | 222 |

| SI no | Item/Job description | External users charge rate | | | Internal users Charge Rates (RS) |
|-------|---|----------------------------|------------------|-------------------------------|---|
| | | Per Job/Item | Industry (RS) | Educational Institute (RS) | |
| | D) Extractor length 60 cm, diameter 25 mm | 1 | 1500 | 900 | 300 |
| | E) Extractor length 60 cm, diameter 40 mm | 1 | 2635 | 1581 | 527 |
| 66 | Chromatography columns plain with PTFE key | | | | |
| | A) Length 20cm diameter 10mm | 1 | 775 | 465 | 155 |
| | B) Length 30cm diameter 15mm | 1 | 980 | 588 | 196 |
| | C) Length 50cm diameter 20mm | 1 | 5815 | 3489 | 227 |
| | D) Length 60cm diameter 25mm | 1 | 1680 | 1008 | 336 |
| | E) Length 60cm diameter 40mm | 1 | 2250 | 1350 | 615 |
| 67 | Essential oil determination unit flask 1000ml capacity, Condenser size 30mm | 1 | 9870 | 5922 | 1974 |
| 68 | Weighing bottle luges for weighing corrosive liquid's | 1 | 1835 | 1101 | 367 |
| 69 | Short path distillation set (without thermometer) Thermometer pocket | 1 | 9000 | 5400 | 1800 |
| 70 | Gas collecting tube | | | | |
| | A) 125ml | 1 | 1860 | 1116 | 372 |
| | B) 250ml | 1 | 2505 | 1503 | 501 |
| 71 | Coil condenser(distillate type) | | | | |
| | A) Socket size 24/29 cone 24/29 Length 250mm | 1 | 2405 | 1443 | 481 |
| | D) Socket size 24/29 cone 24/29 Length 300mm | 1 | 2740 | 1644 | 548 |
| | E) Socket size 24/29 cone 24/29 Length 400mm | 1 | 3075 | 1845 | 615 |
| 72 | Coil condenser (Reversible type) | | | | |
| | A) Cone size 19/26-24/29 Length 150mm | 1 | 2505 | 1503 | 501 |
| | B) Cone size 24/29-24/29 Length 150mm | 1 | 2680 | 1608 | 536 |
| | C) Cone size 24/29-34/35 Length 150mm | 1 | 2990 | 1794 | 598 |
| 73 | Coil condenser (Grahams type) | | | | |
| | A) Length 200mm | 1 | 1785 | 1071 | 357 |
| | B) Length 300mm | 1 | 2120 | 1272 | 424 |
| 74 | Reflux assembly consists of round bottom flask 1000ml and reversible coil condenser | 1 | 5040 | 3024 | 1008 |
| 75 | Distillation apparatus ammonia 500ml KJELDAHL flask, Splash head and Grahams coil condenser | 1 | 6460 | 3876 | 1292 |