

(केंद्रीय विश्वविद्यालय /A Central University)

• कुलाध्यक्ष का सर्वोत्तम विश्वविद्यालय पुरस्कार,2016 और एनआईआरएफ़ भारत रैंकिंग 2016: नं. 05

• Visitor's Best University Award, 2016 and NIRF India Ranking 2016: No. 05

कुल सचिव का कार्यालय / OFFICE OF THE REGISTRAR

तेजपुर-784028 :: असम / TEZPUR-784028 :: ASSAM

SHORT QUOTATION NOTICE

TU/11-24/Pur/Qtn/2016-17/4822 dated:-14.02.2017.

Sealed quotations are invited from reputed manufacturers/authorized dealers/vendors for supply and installation of CCTV cameras required for Tezpur University.

List of Items with Specifications:

	Titems with Specifications V Specifications	
1	2 MP Bullet Camera	
-	Parameter	Minimum Desired Specifications
	Image Sensor	2MP CMOS Image Sensor
	Pixels	1920(H)*1080(V)
	Resolution	2 MP
	Min. Illumination	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR
	S/N Ratio	≥ 48dB
	Lens	3.6 mm
	White Balance (AWB)	Auto
	Gain Control (AGC)	Auto
	Back Light Compensation	Auto
	IR	12 LEDs, Upto 20 Mtrs
	Video Frame Rate	1080p@25fps/1080p@30fps
	Power Supply	DC 12V ± 5%
	Power Consumption	<5W
	IP Rating	IP66 Rated Enclosure
	Operating Temperature	-40 °C – 60 °C (-40 °F – 140 °F), Humidity 90% or less (non-condensing)
	Certifications	CE, FCC
2	2 MP Dome Camera	
	Parameter	Minimum Desired Specifications
	Image Sensor	2MP CMOS Image Sensor
	Pixels	1920(H)*1080(V)
	Resolution	2 MP
	Min. Illumination	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR
	S/N Ratio	≥ 48dB
	Lens	3.6 mm
	White Balance (AWB)	Auto
	Gain Control (AGC)	Auto
	Back Light Compensation	Auto
	IR	12 LEDs, Upto 20 Mtrs
	Video Frame Rate	1080p@25fps/1080p@30fps
	Power Supply	DC 12V ± 5%
	Power Consumption	<5W
	IP Rating	IP66 Rated Enclosure
	Operating Temperature	-40 °C – 60 °C (-40 °F – 140 °F), Humidity 90% or less (non-condensing)



(केंद्रीय विश्वविद्यालय /A Central University)

• कुलाध्यक्ष का सर्वोत्तम विश्वविद्यालय पुरस्कार,2016 और एनआईआरएफ़ भारत रैंकिंग 2016: नं. 05

• Visitor's Best University Award, 2016 and NIRF India Ranking 2016: No. 05

कुल सचिव का कार्यालय / OFFICE OF THE REGISTRAR

तेजपुर-784028 :: असम / TEZPUR-784028 :: ASSAM

	Certifications	CE, FCC	
3	16 CHANNEL 1080p Digital Vide	eo Recorder (DVR)	
	Parameter	Minimum Desired Specifications	
	Operating System	Embedded LINUX	
	System Resources	Pentaplex function: live, recording, playback, backup & remote access	
	Control Devices	Front panel, USB mouse	
	Video Input	BNC interface (1.0Vp-p, 75 Ω), supporting coaxitron connection	
	Video Output	1 HDMI, 1 VGA, 1 TV, 1 Spot, BNC(1.0Vp-p, 75Ω)	
	Video Standard	NTSC(525Line, 60f/s), PAL(625Line, 50f/s)	
	Compression	H.264	
	Video Resolution	1920×1080, 1280×1024, 1280×720, 1024×768, 800×600	
	Video Recording	D1/4CIF@1~25/30fps(704×576/704×480) HD1@1~25/30fps(352×576/352×480) 2CIF@1~25/30fps (704×288/704×240) CIF@1~25/30fps(352×288/352×240) QCIF@1~25/30fps(176×144/176×120)	
	Video Display Split	3 (/)8	
	Privacy Masking	4 self-defined four-sided zones for privacy masking for each camera	
	Audio Input	1 channel, RCA(200-2800mV, 30KΩ)	
	Bi-directional Talk Input	1 channel Input, BNC(200-2800mV, 30KΩ)	
	Audio Output	1 channel, BNC(200-3000mV, 5KΩ)	
	Hard Disk	2 SATA ports, each port suppoting Up to 6TB capacity	
	Surveillance HDD Mgmt	Hard disk hibernation technology, HDD fault alarm	
	Recording Mode	Manual, Scheduled, Motion Based [Regular(Continuous)]	
	Network	10M / 100M / 1000M Auto-sensing Ethernet interface	
4	Storage		
	Parameter	Minimum Desired Specifications	
	Hard Disk Drive(HDD)	SATA 7.2K HDD - 4TB Capacity (Preferred Make: Seagate / Western Digital)	
5	16 Cameras Power Supply		
	Parameter	Minimum Desired Specifications	
	General	 Stabilized Ouptput & Low Interference Surge Protection , Over Temperature, Current, Voltage & Load Protection High efficiency & low energy Consumption Individual output with Reusable Fuse Short Circuit Auto Restart Highly Intergrated SMPS Switcher I.C Design Low Ripple Voltage(mV P-P):<5% 	
	Application	 1. 16 Channel Security Camera Power Supply 2. Power LED Monitor for individual camera channel 3. Individual Camera Drive 	
6	Cable (Roll of 90 Mtrs)	·	
	Parameter	Minimum Desired Specifications	
	Inner Conductor Specifications		



(केंद्रीय विश्वविद्यालय /A Central University)

• कुलाध्यक्ष का सर्वोत्तम विश्वविद्यालय पुरस्कार,2016 और एनआईआरएफ़ भारत रैंकिंग 2016: नं. 05

• Visitor's Best University Award, 2016 and NIRF India Ranking 2016: No. 05

कुल सचिव का कार्यालय / OFFICE OF THE REGISTRAR

तेजपुर-784028 :: असम / TEZPUR-784028 :: ASSAM

	Material	Solid Bare Copper
	Diameter	0.80mm Nom. (20 AWG)
	Dielectric Material	Gas injected Physical foam polyethylene
	Diameter	3.55mm Nom.
	Shield Specifications	
	1st Shield	Bonded Aluminum Tape
	2nd Shield	Aluminium Alloy Braid
	Coverage	Nom. 60%
	Jacket Specifications	
	Material	PVC
	Diameter	5.60mm Approx.
	Bending Radius	65mm Min.
	Electrical Specifications	
	Inner Conductor DC Resistance	Max. 3.55Ohm/Km at 20 Degree C
	Capacitance (Nom.)	53.0pF/m
	Characteristic Impedence	75 ± 3 ohm
	Structural Return Loss	Min. 15 dB @ 1-1000MHz
	Nominal Velocity Ratio	85%
	3 Cores Specifications	
	Conductor	16 x 0.20mm bare annealed copper
	Insulation	PVC, Type A Grade conforming to IS 5831
	Diameter	2.00mm Nom.
	Colour Codes	Yellow, Blue, Red
	Overall Jacket	PVC Type ST1 Grade Conformaing to IS 5831
	Overall Diameter	9.50mm
7	BNC Connector	·
	Parameter	Minimum Desired Specifications
	To comply with the above cable a	nd camera input specifications
8	Power Jack	
	Parameter	Minimum Desired Specifications
		nd camera power input specifications
9	22" LED HD Monitor	
	Parameter	Minimum Desired Specifications
	Screen size	21.5 (54.61 cms)
	Resolution	1920 x 1080
	Brightness (nit)	200 nits
	Response Time(ms)	5ms
	Viewing Angle	90/65
	Color Depth (No. of Colors)	16.7M
	Pixel Pitch(mm)	0.25 x 0.25
	Surface Treatment	Anti - Glare
	Auto Resolution	Support should be available



(केंद्रीय विश्वविद्यालय /A Central University)

• कुलाध्यक्ष का सर्वोत्तम विश्वविद्यालय पुरस्कार,2016 और एनआईआरएफ़ भारत रैंकिंग 2016: नं. 05

• Visitor's Best University Award, 2016 and NIRF India Ranking 2016: No. 05

कुल सचिव का कार्यालय / OFFICE OF THE REGISTRAR

तेजप्र-784028 :: असम / TEZPUR-784028 :: ASSAM

	Wall Mount (VESA)	Should be available (75 x 75)	
	D-Sub	Should be available	
	HDMI	Should be available	
	LED color	White	
	Power Type	External Power Adapter	
	Power Usage	18 W	
	Power Usage while S/W Off	Should be below 0.3 W	
10	Cable Laying Service		
	Parameter		
	Laying of CCTV cable using 19mm PVC Conduit with Accessories [Should comply to ISI Standards]. The installation has to be carried out by qualified technical personnel without damaging the interiors and aesthetics of the building/room. To be quoted in per unit meter .		
11	Installation Job		
	Parameter		
Α	Full Installation job of CCTV Solution with 16 Camera		
В	Full Installation job of CCTV Solution with 8 Camera		
12	Terms & Conditons		
а	The installation job has to be carried out by qualified technical personnel without damaging the interiors and aesthetics of the building.		
b	All cameras have to properly mounted on Ceilings/Walls as per requirement of the University Officials.		
С	All camera positions have to be properly documented and numbered and a layout map have to be provided showing camera positions.		
d	Monitor has to be properly wall fixed with appropriate mountings.		
е	All cables should be tangle free and should be properly marked and should be easily identifiable.		
f	All CCTV cables/BNC connectors/ Power jacks/etc. have to be properly terminated, crimped and sealed. No lose connectors/jacks will be acceptable.		
g	Brief Orientation of the working procedure and troubleshooting has to be provided to the University officials.		
h	All devices i.e. DVR/ HDD/ Camera/ Power Supply/ Monitor should carry one year replacement warranty.		

GENERAL TERMS & CONDITIONS:

- 1. No separate tender paper will be issued from the office; one should only download the specifications/List from the website.
- 2. The rates should be quoted on FOR Tezpur University, Napaam basis.
- 3. Quotations should be accompanied by i)A non refundable application (quotation) fee of ₹.500.00 (Rupees Five Hundrded) only have to be paid only by Demand Draft drawn in favour of Registrar, Tezpur University payable at Tezpur.
- 4. The rates should be exclusive of taxes and applicable tax % should be clearly indicated.
- 5. Quoted rates should be valid for at least one year.
- 6. The rates should be quoted along with supporting documents of specifications and technical features and list of users.
- 7. No Advance payment will be made.
- 8. The warranty of the items should be provided as per specification sheet.
- 9. Payment wil be made after receipt of materials at site in full and in good condition.
- 10. In case of cables, the supplier shall submit the companies cable Test Report along with the Bill. Inspection from University's end is necessary in case of bulk supply of cables.
- 11. Dealership certificate from the manufacturers is required to be submitted along with the quotation.



(केंद्रीय विश्वविद्यालय /A Central University)

• कुलाध्यक्ष का सर्वोत्तम विश्वविद्यालय पुरस्कार,2016 और एनआईआरएफ़ भारत रैंकिंग 2016: नं. 05

• Visitor's Best University Award, 2016 and NIRF India Ranking 2016: No. 05

कुल सचिव का कार्यालय / OFFICE OF THE REGISTRAR

तेजप्र-784028 :: असम / TEZPUR-784028 :: ASSAM

- 12. The University reserves the right to accept or reject any or all the quotations without assigning any reason.
- 13. Apart from the above terms and conditions the University has the right to include any other terms and conditions as and when felt necessary.
- 14. Quotation should be submitted in the DROP BOX placed in the reception of the Administrative Building of the University on or before 07.03.2017. If posted/courierred, should reach on or before 07.03.2017 addressed to "The Joint Registrar, Tezpur University". The Quotation Notice No. and date should be clearly superscribed in the the envelope/packet containing the quotation

Joint Registrar Tezpur University Memo No. TU/11-24/Pur/Qtn/2016-174822-A Copy for information to:-

dated: 14.02.2017

- 1. Webmaster, Tezpur University for uploading the notice in the website.
- 2. File.

Joint Registrar